

Leaded Bronze Alloy, Chill cast, CRM, Disc Ø 40 mm x 15 mm

Art. ID	MBH-32XLB14H
Unit	disc
Deliverydetails	No Dangerous Good /not restricted

Description

These standards would be ideal for use as calibration standards to cover a range of concentrations for XRF, or as type standards for OES.

Text/Information	Analyte/Parameter	CAS number	Concentration/Value	Unit	Method	Source
Batch H	Silver (Ag)	[7440-22-4]	0,046 ± 0,001	%		
Batch H	Aluminium (Al)	[7429-90-5]	0,0008 ± 0,0002	%		
Batch H	Arsenic (As)	[7440-38-2]	0,055 ± 0,001	%		
Batch H	Bismuth (Bi)	[7440-69-9]	0,496 ± 0,006	%		
Batch H	Cadmium (Cd)	[7440-43-9]	0,0005 ± 0,0001	%		
Batch H	Cobalt (Co)	[7440-48-4]	0,0018 ± 0,0001	%		
Batch H	Copper (Cu)	[7440-50-8]	78,4 ± 0,1	%		
Batch H	Iron (Fe)	[7439-89-6]	0,041 ± 0,002	%		
Batch H	Nickel (Ni)	[7440-02-0]	0,3 ± 0,005	%		
Batch H	Phosphorus (P)	[7723-14-0]	0,039 ± 0,001	%		
Batch H	Lead (Pb)	[7439-92-1]	15,04 ± 0,07	%		
Batch H	Sulfur (S)	[7704-34-9]	0,036 ± 0,002	%		
Batch H	Antimony (Sb)	[7440-36-0]	0,103 ± 0,002	%		
Batch H	Silicon (Si)	[7440-21-3]	0,0012 ± 0,0002	%		
Batch H	Tin (Sn)	[7440-31-5]	5,16 ± 0,03	%		
Batch H	Zinc (Zn)	[7440-66-6]	0,254 ± 0,004	%		