

**Sulfur in Mineral Oil, Set of 8 calibration standards, concentrations of 0, 5, 10, 30, 50, 70, 100 and 150 ppm, 100 mL each (Standard for XRF)**

Art. ID ASI-SMO8(OX)-Set(8x100ML)  
Unit 8 x 100 mL  
Deliverydetails No Dangerous Good /not restricted

Text/Information	Analyte/Parameter	CAS number	Concentration/Value	Unit	Method	Source
ASI-SMO8(OX)-01	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	0	ppm	ASTM D7039	
ASI-SMO8(OX)-02	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	5	ppm	ASTM D7039	
ASI-SMO8(OX)-03	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	10	ppm	ASTM D7039	
ASI-SMO8(OX)-04	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	30	ppm	ASTM D7039	
ASI-SMO8(OX)-05	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	50	ppm	ASTM D7039	
ASI-SMO8(OX)-06	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	70	ppm	ASTM D7039	
ASI-SMO8(OX)-07	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	100	ppm	ASTM D7040	
ASI-SMO8(OX)-08	Sulfur (S) (as Di-n-butyl sulfide)	[544-40-1]	150	ppm	ASTM D7041	